

□ □ □ □ (□ □ □ □ □)

B610342

[illegible]

/// □ □ □ □ □ □ □ □ ///

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ □ □ □ □ □



危險



報告



注意

□ □ □ □ □ □ □ □ □ □ □ □



● 危險

[illegible]



□ □ □ □ □ □ □ □



□ □ □ □ □ □ □ □

B610342 - 2

□ □ □ □ □ □						□ □	□ □ □ □ □ □						□ □	
①	□	□	□	□	□	□	2	②	□	□	□	□	□	2
③	□	□	□	□	□	□ M- 20	8	④	□	□	□	□	M- 20	4
⑤	□	□	□	□	□		8	⑥	□	□	□	□	/ □ □	3

1. $\square \square$
 $\square \square \square \square \square \square$
2. $\square \square$
 $\textcircled{5} \square \square \square \square \square \square \square \square \square$

1. □□□□□□□□□□□□①□□□□□□□□□□
□□□□□□□

1. □□□□□□□□ (□□□□□□□□□□□□□□□) □□□
□□□□□□□□□□□□

* □

This diagram illustrates the installation of a metal bracket to the underside of a vehicle body. A bolt is shown passing through a pre-drilled hole in the bracket and into the vehicle's body panel. A washer is placed between the bracket and the body panel, and a nut is threaded onto the bolt from the underside. Arrows indicate the direction of assembly: the bolt is inserted from the bracket, the washer is placed against the body, and the nut is tightened from below.

□ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ □ ⑤

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

□ □ □ □ □ □ ④

[illegible]

-